


PROPERTY SURVEY FOR
DUCHESNE COUNTY
SECTION 6, TOWNSHIP 3 SOUTH, RANGE 4 WEST
UINTAH SPECIAL BASE AND MERIDIAN
DUCHESNE COUNTY, UTAH



SURVEYOR'S CERTIFICATE

THIS SURVEY WAS PERFORMED AT THE REQUEST OF DUCHESNE COUNTY FOR THE PURPOSE OF LOCATING THE CORNERS OF THE NE 1/4 OF THE SE 1/4 OF THE NW 1/4 OF SECTION 6 AS SHOWN ON THIS PLAT.

THIS SECTION WAS ORIGINALLY SURVEYED BY THE GENERAL LAND OFFICE IN 1883 USING THE "3-MILE METHOD" OF SECTION SUBDIVISION AND SETTING STONE CORNERS. THE EXTERIOR SECTION LINES WERE RESURVEYED BY THE G.L.O. IN 1916 SETTING BRASS CAPS ON IRON PIPE MONUMENTS.

A SEARCH WAS MADE FOR ALL OF THE ALIQUOT PART CORNERS. MANY OF THE 1916 MONUMENTS WERE FOUND AND NOTED ON THE PLAT. NONE OF THE 1883 STONE CORNERS WERE FOUND. SEVERAL REBAR MONUMENTS WERE FOUND AT THE ALIQUOT PART POSITIONS DETERMINED BY USING THE STANDARD SECTION BREAKDOWN METHOD. SOME OF THESE REBAR MONUMENTS WERE SET BY THIS SURVEYOR IN 1986 WHILE SURVEYING THE SAME PARCEL FOR THE COUNTY USING THE STANDARD METHOD OF SECTION SUBDIVISION.

THE "3-MILE METHOD" WAS GENERALLY UNKNOWN BY THE SURVEYING PROFESSION AT THE TIME AND WAS NOT ADDRESSED IN THE MANUAL OF SURVEYING INSTRUCTIONS 1973. LATER RESEARCH, MOST NOTABLY BY NELSON MARSHALL, BROUGHT TO LIGHT INFORMATION FROM THE BUREAU OF LAND MANAGEMENT REGARDING THE "3-MILE METHOD" WHICH WAS USED AS AN ALTERNATE PROCEDURE ON SURVEYS PERFORMED ON INDIAN RESERVATIONS BY THE GENERAL LAND OFFICE.


THE 1916 G.L.O. RESURVEY NOTED THAT THE BOUNDARIES OF THE SECTIONS REMAINED UNCHANGED FROM THE 1883 SURVEY AND THAT THE LANDS WOULD CONTINUE TO BE DISPOSED OF BY THE 1883 PLAT. THEREFORE, THE "3-MILE METHOD" WOULD BE THE CORRECT WAY THE SECTION SHOULD HAVE BEEN SUBDIVIDED. HOWEVER, BECAUSE MANY PROPERTY CORNERS HAVE BEEN SET AND LINES OF POSSESSION ESTABLISHED OVER THE YEARS IT DOES NOT SEEM WISE TO TRY TO USE THE "3-MILE METHOD" AND DISRUPT THE SETTLED PROPERTY LINES ALREADY IN PLACE. THEREFORE, THE FOUND REBAR MONUMENTS WERE HELD AND USED TO CONTROL THIS SURVEY, FALLING BACK ON THE STANDARD METHOD.

LEGEND

- FOUND MONUMENT AT SECTION CORNER
- FOUND MONUMENT AT QUARTER CORNER
- FOUND MONUMENT AT CLOSING CORNER
- FOUND REBAR AT 1/16 CORNER
- FOUND REBAR AT PROPERTY CORNER

SURVEYOR'S CERTIFICATE

This is to certify that this plat was prepared from the field notes and electronic data collector files of an actual survey made by me, or under my personal supervision, of the parcels of land shown hereon, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.



Jerry D. Allred, Professional Land Surveyor
Utah Certificate Number 148951